MOBILE LED PROMOTIONAL COUNTER

Vendora Series

A portable, LED-wrapped promotional counter — powered by Naxora Vista fine-pitch indoor screens.

OVERVIEW

Your brand, on wheels

The Vendora Series turns any retail floor, exhibition, lobby, or event into a branded moment. A powder-coated steel counter body wraps a front panel and two curved side panels in Naxora Vista fine-pitch indoor LED — delivering crisp, close-range visuals that printed graphics simply can't match.

Lockable storage at both ends, a secure central drawer, and four braked casters make it a true plug-in-and-promote unit that one person can reposition in seconds.

FEATURES

Key capabilities

- Three-face LED wrap — front + two curved side panels for 270° brand visibility
- Powered by Naxora Vista fine-pitch (P1.25–P2.5) indoor LED
- Powder-coated steel body with lockable storage at both ends
- Secure central locking drawer plus an open service shelf
- Four braked, floor-safe casters — reposition in seconds
- Tool-free front-service LED access; single plug-and-play power feed

1.25–2.5 mm	600 nits	6000:1	14-bit	3 Faces	100,000 h
Pixel Pitch	Brightness	Contrast	Greyscale	LED Wrap	LED Life

WHY VENDORA

Vendora Series advantages

270° three-face wrap

Front plus two curved side panels put your brand in view from every approach angle.

Fine-pitch clarity

Naxora Vista P1.25–P2.0 delivers seamless, close-range visuals with no visible pixels.

Secure & mobile

Lockable end cabinets, a locking drawer, and four braked casters — move it, lock it, leave it.

Front-service ready

Tool-free front access to LED modules and cabling — service without moving the counter.

AVAILABLE MODELS

Four fine-pitch configurations

Vendora 1.25	Vendora 1.53	Vendora 1.86	Vendora 2.0	Vendora 2.5
P1.25 • SMD1010	P1.53 • SMD1212	P1.86 • SMD1515	P2.0 • SMD1515	P2.5 • SMD1515/SMD2121
640,000 dot/m²	422,500 dot/m²	288,906 dot/m²	250,000 dot/m²	160,000 dot/m²

LED DISPLAY

LED display specifications

Naxora Vista fine-pitch models used on the Vendora wrap.

Parameter	Vendora 1.25	Vendora 1.53	Vendora 1.86	Vendora 2.0	Vendora 2.5
Model code	FIK-NXI 1.25	FIK-NXI 1.53	FIK-NXI 1.86	FIK-NXI 2.0	FIK-NXI 2.5
Pixel Pitch (mm)	1.25	1.53	1.86	2.0	2.5
Pixel Density (dot/m²)	640,000	422,500	288,906	250,000	160,000
SMD Type	SMD1010	SMD1212	SMD1515	SMD1515	SMD1515 / 2121
Module Resolution	256×128	208×104	172×86	160×80	128×64
Scan Mode	64S	52S	43S	40S	32S
Brightness (cd/m²)	550	550	550	550	550
Max Power (W/m²)	≤390.6	≤341.8	≤371.1	≤390.6	≤371.1
Avg Power (W/m²)	≤130.2	≤113.9	≤123.7	≤130.2	≤123.7
Module Weight (kg/m²)	20.2	20.2	20.2	20.2	20.2

COMMON LED

Common LED specifications

Parameter	Specification
Module Size	320 × 160 mm
Contrast Ratio	6000:1
Horizontal Viewing	140 ± 10°
Vertical Viewing	130 ± 10°
Grey Scale	14-bit / 16-bit
Refresh Rate	3840 Hz / 7680Hz
Input Voltage	AC 100–240 V
Ingress Protection	IP4X
Maintenance / Install	Front / Front
Control System	Sync / Async
Life Span	100,000 hours

CABINET

Cabinet & counter

Parameter	Specification
Counter Body	Powder-coated steel, matte black
Overall W×H×D	2240 × 1280 × 500 mm
Display Faces	Front + 2 curved side panels
Storage	2 lockable end cabinets
Drawer	1 central locking drawer + shelf
Mobility	4 × braked casters
Net Weight *	≈ 95 kg
Power Input	Single AC feed, 100–240 V
Service Access	Tool-free, front
Finish Options	Custom brand colours
Certifications	BIS, CE, CB, FCC, ETL

PLATFORM

Naxora platform highlights

Unified module architecture

One 320 × 160 mm module across every pitch — common spares, common service.

Multi-region certified

BIS, CE (LVD & EMC), CB, FCC and ETL — deployment-ready across markets.

Built for 100,000 hours

Industrial-grade PCB and rigorous component selection for years of reliable use.

Asta CMS integration

Optional FutureIK Asta CMS for AI content, scheduling and audience analytics.

ENVIRONMENT

Environment & operation

Parameter	Specification
Working Temperature	0 °C to +40 °C
Storage Temperature	0 °C to +50 °C
Working Humidity	10 – 95 % RH
Input Voltage	AC 100–240 V
LED Life Span	100,000 hours
Warranty	2 Years

APPLICATIONS

Where it shines

- **Retail & Showrooms**
  Storefront promos, product feature zones, POS moments.
- **Exhibitions & Trade Shows**
  Portable stands, demo counters, brand activations.
- **Hotel & Mall Lobbies**
  Reception desks, wayfinding, welcome displays.
- **Events & Roadshows**
  Registration counters, sampling booths, pop-ups.

CONFIGURATION

Build & options

LED face options

Front + two curved sides as standard; front-only or single-side wraps on request.

Finish & branding

Powder-coated steel in custom brand colours with printed side-panel graphics.

Storage & security

Twin lockable end cabinets, a central locking drawer and four braked casters.

COMPLIANCE

Global certifications

BIS
Certified

CE (LVD & EMC)
Certified

CB
Certified

FCC
Certified

ETL
Certified

Ready to deploy?

Tell us your viewing distance, environment, and content goals — we'll spec the right Naxora configuration and walk you through deployment.

EMAIL OUR SALES TEAM

sales@futureik.com

CALL US • INDIA

+91 76192 03418